

Globetrotter® IEC (Metric) Frame, Three Phase

Totally Enclosed, Flange/Base Mounting

Multiplier Symbol F4

B3/B5 "FF" (D-Flange)

HP/Kw	RPM 60/50 HZ	60 HZ VOLTS	50 HZ VOLTS	IEC FRAME	CAT NO.	MODEL NO.	STOCK	CT SPEED RANGE ☆	LIST PRICE	NOM. EFF.	60 HZ F.L. AMPS	WEIGHT	IEC "L" DIM. (MM)	FOOT NOTES
1/4-18	3600/3000	230/460	200/400	63D	R380	63T34FH5501	*	20:1	\$215	72.0	0.8/0.4	10	217	
	1800/1500	230/460	200/400	63D	R381	63T17FH5502	*	20:1	\$222	68.0	1.0/0.5	11	217	
	1200/1000	230/460	200/400	71D	R382	71T11FH5503	*	20:1	\$382	64.0	1.2/0.6	12	240	
1/3-25	3600/3000	230/460	200/400	63D	R383	63T34FH5504	*	20:1	\$249	72.0	1.1/1.55	11	217	
	1800/1500	230/460	200/400	71D	R384	71T17FH5505	*	20:1	\$257	68.0	1.4/1.7	13	240	
	1200/1000	230/460	200/400	80D	R385	80T11FH5506	*	20:1	\$410	70.0	1.3/1.65	17	282	
1/2-37	3600/3000	230/460	200/400	71D	R386	71T34FH5507	*	20:1	\$255	74.0	1.6/1.8	13	240	
	1800/1500	230/460	200/400	71D	R387	71T17FH5508	*	20:1	\$264	74.0	1.8/1.9	14	282	
	1200/1000	230/460	200/400	80D	R388	80T11FH5509	*	20:1	\$427	72.0	1.9/1.95	19	282	
3/4-55	3600/3000	230/460	200/400	71D	R389	71T34FH5510	*	20:1	\$270	74.0	2.4/1.2	15	282	
	1800/1500	230/460	200/400	80D	R390	80T17FH5511	*	20:1	\$288	74.0	2.5/1.25	18	282	
	1200/1000	230/460	200/400	80D	R391	80T11FH5512	*	20:1	\$452	72.0	2.7/1.35	22	320	
1-75	3600/3000	230/460	200/400	80D	R392	80T34FH5513	*	20:1	\$297	75.5	2.8/1.4	21	282	
	1800/1500	230/460	200/400	80D	R393	80T17FH5514	*	20:1	\$311	80.0	3.2/1.6	26	282	
	1200/1000	230/460	200/400	90SD	R394A	90ST11FH6515	*	20:1	\$556	82.5	3.3/1.7	35	320	68
1 1/2-1.1	3600/3000	230/460	200/400	80D	R395	80T34FH5516	*	20:1	\$339	84.0	4.0/2.0	30	282	
	1800/1500	230/460	200/400	90SD	R396A	90ST17FH6517	*	20:1	\$403	86.5	4.6/2.3	37	320	68
2-1.5	3600/3000	230/460	200/400	90SD	R397A	90ST34FH6518	*	20:1	\$439	85.5	5.2/2.6	33	320	68
	1800/1500	230/460	200/400	90LD	R398A	90LT17FH6519	*	20:1	\$451	86.5	5.8/2.9	38	320	68
	3-2.2	3600/3000	230/460	90LD	R399A	90LT34FH6520	*	20:1	\$621	86.5	7.2/3.6	39	320	68

B3/B14 "FT" (C-Face)

HP/Kw	RPM 60/50 HZ	60 HZ VOLTS	50 HZ VOLTS	IEC FRAME	CAT NO.	MODEL NO.	STOCK	CT SPEED RANGE ☆	LIST PRICE	NOM. EFF.	60 HZ F.L. AMPS	WEIGHT	IEC "L" DIM. (MM)	FOOT NOTES
1/4-18	3600/3000	230/460	200/400	63C	R360	63T34FH5401	*	20:1	\$211	72.0	0.8/0.4	10	217	
	1800/1500	230/460	200/400	63C	R361	63T17FH5402	*	20:1	\$219	68.0	1.0/0.5	11	217	
	1200/1000	230/460	200/400	71C	R362	71T11FH5403	*	20:1	\$382	64.0	1.2/0.6	12	240	
1/3-25	3600/3000	230/460	200/400	63C	R363	63T34FH5404	*	20:1	\$247	72.0	1.1/1.55	11	217	
	1800/1500	230/460	200/400	71C	R364	71T17FH5405	*	20:1	\$250	68.0	1.4/1.7	13	240	
	1200/1000	230/460	200/400	80C	R365	80T11FH5406	*	20:1	\$410	70.0	1.3/1.65	17	282	
1/2-37	3600/3000	230/460	200/400	71C	R366	71T34FH5407	*	20:1	\$251	74.0	1.6/1.8	13	240	
	1800/1500	230/460	200/400	71C	R367	71T17FH5408	*	20:1	\$261	74.0	1.8/1.9	14	282	
	1200/1000	230/460	200/400	80C	R368	80T11FH5409	*	20:1	\$427	72.0	1.9/1.95	19	282	
3/4-55	3600/3000	230/460	200/400	71C	R369	71T34FH5410	*	20:1	\$264	74.0	2.4/1.2	15	282	
	1800/1500	230/460	200/400	80C	R370	80T17FH5411	*	20:1	\$283	74.0	2.5/1.25	18	282	
	1200/1000	230/460	200/400	80C	R371	80T11FH5412	*	20:1	\$452	72.0	2.7/1.35	22	320	
1-75	3600/3000	230/460	200/400	80C	R372	80T34FH5413	*	20:1	\$291	75.5	2.8/1.4	21	282	
	1800/1500	230/460	200/400	80C	R373	80T17FH5414	*	20:1	\$304	80.0	3.2/1.6	26	282	
	1200/1000	230/460	200/400	90SC	R374A	90ST11FH6415	*	20:1	\$556	82.5	3.3/1.7	35	320	68
1 1/2-1.1	3600/3000	230/460	200/400	80C	R375	80T34FH5416	*	20:1	\$331	84.0	4.0/2.0	30	282	
	1800/1500	230/460	200/400	90SC	R376A	90ST17FH6417	*	20:1	\$395	86.5	4.6/2.3	37	320	68
2-1.5	3600/3000	230/460	200/400	90SC	R377A	90ST34FH6418	*	20:1	\$430	85.5	5.2/2.6	33	320	68
	1800/1500	230/460	200/400	90LC	R378A	90LT17FH6419	*	20:1	\$439	86.5	5.8/2.9	38	320	68
	3-2.2	3600/3000	230/460	90LC	R379A	90LT34FH6420	*	20:1	\$621	86.5	7.2/3.6	39	320	68

† Requires nameplate modification

Catalog numbers (Cat No.) highlighted in bold blue have efficiency levels that meet EISA requirements