

# EXPANDED OFFERING:

# 6-POLE GENERATORS

- Continuous Duty
- 20 to 1500 kW
- 1200 RPM

**60  
Hertz**

**6-Pole,  
Three Phase,  
Broad Range**

208Y-240Y or 416Y-480Y Volts  
240 or 120 Volts Delta

NEMA Class F Insulation  
40°C Ambient  
0.8 p.f.  
SE350 AVR, Shunt Excitation



## LIMA SER®

Base Model	Net Wt. (lbs.)	No. of Leads	kW Rating Continuous		
			NEMA B 80°C R/R	NEMA F 105°C R/R	NEMA H 125°C R/R
361SSL0105	580	12	21	23	N/A
361SSL0107	605	12	32	35	N/A
361SSL0108	685	12	42	45	N/A
441SSL0109	885	12	55	61	N/A
441SSL0110	970	12	67	75	N/A
441SSL0111	1035	12	75	81	N/A
441SSL0112	1185	12	103	112	N/A

**60  
Hertz**

**6-Pole,  
Three Phase,  
Broad Range**

208Y-240Y or 416Y-480Y Volts

NEMA Class H Insulation  
40°C Ambient  
0.8 p.f.  
DVR2000+ AVR with PMG

## MAGNAMAX<sup>DVR</sup>

Frame	Net Wt. (lbs.)	No. of Leads	kW Rating Continuous		
			NEMA B 80°C R/R	NEMA F 105°C R/R	NEMA H 125°C R/R
572	2050	12	160	180	200
572	2204	12	200	230	250
572	2502	12	250	290	315
573	2976	12	300	348	380
573	3417	12	400	460	500
574	4144	12	500	578	630
742	6488	6	600	690	750
742	7438	6	730	915	1000
743	8708	6	925	1150	1250
744	9340	6	1100	1375	1500



**MARATHON ELECTRIC**  
GENERATORS

# EXPANDED OFFERING:

# 6-POLE GENERATORS

- Continuous Duty
- 20 to 1500 kVA
- 1000 RPM

**50  
Hertz**

**6-Pole,  
Three Phase,  
Broad Range**

190Y-208Y or 380Y-415Y Volts  
220 or 110 Volts Delta

NEMA Class F Insulation  
40°C Ambient  
0.8 p.f.  
SE350 AVR, Shunt Excitation



## LIMA SER®

Base Model	Net Wt. (lbs.)	No. of Leads	kVA Rating Continuous		
			NEMA B 80°C R/R	NEMA F 105°C R/R	NEMA H 125°C R/R
361SSL0105	580	12	19	20	N/A
361SSL0107	605	12	29	31	N/A
361SSL0108	685	12	39	45	N/A
441SSL0109	885	12	48	53	N/A
441SSL0110	970	12	63	71	N/A
441SSL0111	1035	12	66	75	N/A
441SSL0112	1185	12	103	113	N/A

**50  
Hertz**

**6-Pole,  
Three Phase,  
Broad Range**

190Y-208Y or 380Y-415Y Volts

NEMA Class H Insulation  
40°C Ambient  
0.8 p.f.  
DVR2000E+ AVR with PMG

## MAGNAMAX<sup>DVR</sup>

Frame	Net Wt. (lbs.)	No. of Leads	kVA Rating Continuous		
			NEMA B 80°C R/R	NEMA F 105°C R/R	NEMA H 125°C R/R
572	2050	12	160	180	200
572	2204	12	200	231	250
572	2502	12	250	288	313
573	2976	12	300	344	375
573	3417	12	400	456	500
574	4144	12	500	575	625
742	6488	6	600	688	750
742	7438	6	800	919	1000
743	8708	6	1000	1144	1250
744	9340	6	1200	1375	1500



**MARATHON ELECTRIC**  
GENERATORS